

GRINDING & SANDING

Pneumatic Grinder

MYTON

Heavy-duty grinders for tough applications

- Side exhaust with noise reduction system
- Great power/weight ratio


Model MYG-25

For Grinding Wheel 58 mm
Compact and lightweight type




Model MYG-40

For Grinding Wheel 100 mm
Powerful type



Model MAGW-40

Lever switch type
Depressed center wheel 100 mm



Model MAGW-40 Non-CE

Ring switch type
Depressed center wheel 100 mm




Specifications

Model	MYG-25	MYG-40	MAGW-40 Lever Type	MAGW-40 Ring Type
Air Pressure	MPa (kgf/cm ²)	0.6 (6)		
Air Consumption	m ³ /min	0.42 (No-load)	0.50 (No-load) 0.69 (Load)	0.68 (No-load) 0.82 (Load)
Free Speed	min ⁻¹ (rpm)	19000	13000	
Depressed Center Grinding Wheel	mm	58	100	
Inlet Size		Rc 1/4	Rc 3/8	
Mass (Weight)	kg	0.6	1.5	
Accessories Included	<ul style="list-style-type: none"> • 5 mm Hex. Socket Screw Key • 19 mm Single Ended Spanner • Grinding Wheel GS #80 x 58 • Bushing R 1/4 x NPT 1/4 	<ul style="list-style-type: none"> • 5 mm Hex. Socket Screw Key • 6 mm Hex. Socket Screw Key • Bushing R 3/8 x NPT 3/8 	<ul style="list-style-type: none"> • 6 mm Hex. Socket Screw Key • 17 mm Single Ended Spanner • Bushing R 3/8 x NPT 3/8 	


Model MYG-50

Lever switch type
For Grinding wheel 125 mm
Heavy grinding type



Model MYG-70

Lever switch type
For Grinding wheel 180 mm
Heavy grinding type



Model MYG-70 Non-CE

Ring switch type
For Grinding wheel 180 mm
Heavy grinding type



Specifications

Model	MYG-50	MYG-70 Lever Type	MYG-70 Ring Type
Air Pressure	MPa (kgf/cm ²)	0.6 (6)	
Air Consumption	m ³ /min	0.75 (No-load)	0.70 (No-load) 0.95 (Load)
Free Speed	min ⁻¹ (rpm)	11000	7600
Depressed Center Grinding Wheel	mm	125	180
Inlet Size		Rc 3/8	
Mass (Weight)	kg	2.5 (with handle)	2.4 (with handle)
Accessories Included	<ul style="list-style-type: none"> • Handle (anti-vibration type) • 4 mm Hex. Socket Screw Key • 6 mm Hex. Socket Screw Key • Pin Face Wrench • Bushing R 3/8 x NPT 3/8 	<ul style="list-style-type: none"> • Handle • 6 mm Hex. Socket Screw Key • 10 mm Hex. Socket Screw Key • Bushing R 3/8 x NPT 3/8 	<ul style="list-style-type: none"> • Handle • 6 mm Hex. Socket Screw Key • 10 mm Hex. Socket Screw Key • Bushing R 3/8 x NPT 3/8